

# A demonstration of the nproc package

*Yang Feng, Jessica Li and Xin Tong*

*2016-06-18*

We provide a detailed demo of the usage for **nproc** package.

Introduction

Installation and Package Load

Neyman-Pearson Classification

Neyman-Pearson Receiver Operator Curve

## Introduction

Let  $(X, Y)$  be random variables where  $X \in \mathcal{X}$  is a vector of  $d$  features and  $Y \in \{0, 1\}$  represents a binary class label. A data set that contains independent observations  $\{(x_i, y_i)\}_{i=1}^{n+m}$  sampled from the joint distribution of  $(X, Y)$  are often divided into training data  $\{(x_i, y_i)\}_{i=1}^n$  and test data  $\{(x_i, y_i)\}_{i=n+1}^{n+m}$ .

Based on training data, a *classifier*  $\phi(\cdot)$  is a mapping  $\phi: \mathcal{X} \rightarrow \{0, 1\}$  that returns the predicted class label given  $X$ . Classification error occurs when  $\phi(X) \neq Y$ , and the binary loss is defined as  $1(\phi(X) \neq Y)$ , where  $1(\cdot)$  denotes the indicator function. The risk is defined as  $R(\phi) = E[1(\phi(X) \neq Y)] = P(\phi(X) \neq Y)$ , which can be expressed as a weighted sum of type I and II errors:  $R(\phi) = P(Y = 0)R_0(\phi) + P(Y = 1)R_1(\phi)$ , where  $R_0(\phi) = P(\phi(X) \neq Y | Y = 0)$  denotes the type I error, and  $R_1(\phi) = P(\phi(X) \neq Y | Y = 1)$  denotes the type II error.

The classical classification paradigm aims to find an oracle classifier  $\phi^*$  by minimizing the risk,  $\phi^* = \arg \min_{\phi} R(\phi)$ .

In contrast, the NP classification paradigm aims to mimic the NP oracle classifier  $\phi_{\alpha}^*$  with respect to a pre-specified type I error upper bound  $\alpha$ ,  $\phi_{\alpha}^* = \arg \min_{\phi: R_0(\phi) \leq \alpha} R_1(\phi)$ , where  $\alpha$  reflects users' conservative attitude (priority) towards the type I error.

Back to Top

## Installation and Package Load

Like many other R packages, the simplest way to obtain **nproc** is to install it directly from CRAN. Type the following command in R console:

```
install.packages("nproc", repos = "http://cran.us.r-project.org")
```

Users may change the **repos** options depending on their locations and preferences. Other options such as the directories where to install the packages can be altered in the command. For more details, see `help(install.packages)`.

Here the R package has been downloaded and installed to the default directories.

Alternatively, users can download the package source at <http://cran.r-project.org/web/packages/nproc/index.html> and type Unix commands to install it to the desired location.

Then we can load the **nproc** package:

```
library(nproc)
```

[Back to Top](#)


## Neyman-Pearson Classification

Here, we provide a demonstration of Neyman-Pearson Classification with a type-I error control. In the first step, we create a dataset (x,y) from a logistic regression model with 2 features and sample size 1000.

```
n = 1000
set.seed(0)
x = matrix(rnorm(n*2),n,2)
c = 1+3*x[,1]
y = rbinom(n,1,1/(1+exp(-c)))
```

A visualization of the two classes.

```
plot(x[y==1,],col=1,xlim=c(-4,4),xlab='x1',ylab='x2')
points(x[y==0,],col=2,pch=2)
legend("topright",legend=c('Class 1','Class 0'),col=1:2,pch=c(1,2))
```



Then, the `npc` function can be called to perform the Neyman-Pearson Classification (`npc`). If one would like to use Linear Discriminant Analysis as the classifier, we can set `method = "lda"`. The default type I error control is `alpha=0.05`. The `alpha` value can be changed to any desirable type I error upper bound in (0, 1).

```
fit = npc(x, y, method = "lda", alpha = 0.05)
```

We can now evaluate the prediction performance of the NP classifier on a test set (`xtest`, `ytest`) generated as follows.

```
xtest = matrix(rnorm(n*2),n,2)
ctest = 1+3*xtest[,1]
ytest = rbinom(n,1,1/(1+exp(-ctest)))
```

We calculate the overall accuracy of the classifier as well as the realized Type I error. It is shown that the Type I error is smaller than  $\alpha$ .

```
pred = predict(fit,xtest)
fit.score = predict(fit,x)
accuracy = mean(pred$pred.label==ytest)
cat("Overall Accuracy: ", accuracy,'\n')
```

```
## Overall Accuracy: 0.691
```

```
ind0 = which(ytest==0)
typeI = mean(pred$pred.label[ind0]!=ytest[ind0]) #type I error on test set
cat('Type I error: ', typeI, '\n')
```

```
## Type I error: 0.0156658
```

The classification method implemented in the `npc` function includes the following options.

- logistic: Logistic regression. `glm` function with family = 'binomial'
- penlog: Penalized logistic regression with LASSO penalty. `glmnet` in `glmnet` package
- svm: Support Vector Machines. `svm` in `e1071` package
- randomforest: Random Forest. `randomForest` in `randomForest` package
- lda: Linear Discriminant Analysis. `lda` in `MASS` package
- nb: Naive Bayes. `naiveBayes` in `e1071` package
- ada: Ada-Boost. `ada` in `ada` package
- custom: a custom classifier

Now, we can try to change the method to logistic regression and change  $\alpha$  to 0.1.

```
fit = npc(x, y, method = "logistic", alpha = 0.1)
pred = predict(fit,xtest)
accuracy = mean(pred$pred.label==ytest)
cat("Overall Accuracy: ", accuracy,'\n')
```

```
## Overall Accuracy: 0.795
```

```
ind0 = which(ytest==0)
typeI = mean(pred$pred.label[ind0]!=ytest[ind0]) #type I error on test set
cat('Type I error: ', typeI, '\n')
```

```
## Type I error: 0.06005222
```

The package also provides implementation of the ensemble classifier. One can set the value `split` to the number of splits. Here, we try to change the number to 11.

```
fit = npc(x, y, method = "logistic", alpha = 0.1, split = 11)
pred = predict(fit, xtest)
accuracy = mean(pred$pred.label == ytest)
cat("Overall Accuracy: ", accuracy, '\n')
```

```
## Overall Accuracy: 0.796
```

```
ind0 = which(ytest == 0)
typeI = mean(pred$pred.label[ind0] != ytest[ind0]) #type I error on test set
cat('Type I error: ', typeI, '\n')
```

```
## Type I error: 0.06005222
```

Let's see the performance of this dataset using all implemented methods as a comparison.

```
methodlist = c("logistic", "penlog", "svm", "randomforest",
               "lda", "nb", "ada")

for(method in methodlist){
  fit = npc(x, y, method = method, alpha = 0.05)
  pred = predict(fit, xtest)
  accuracy = mean(pred$pred.label == ytest)
  cat(method, ': Overall Accuracy: ', accuracy, '\n')
  ind0 = which(ytest == 0)
  typeI = mean(pred$pred.label[ind0] != ytest[ind0]) #type I error on test set
  cat(method, ': Type I error: ', typeI, '\n')
}
```

```
## logistic : Overall Accuracy: 0.69
## logistic : Type I error: 0.0156658
## penlog : Overall Accuracy: 0.701
## penlog : Type I error: 0.0156658
## svm : Overall Accuracy: 0.519
## svm : Type I error: 0.03394256
## randomforest : Overall Accuracy: 0.626
## randomforest : Type I error: 0.02610966
## lda : Overall Accuracy: 0.691
## lda : Type I error: 0.0156658
## nb : Overall Accuracy: 0.695
## nb : Type I error: 0.0156658
## ada : Overall Accuracy: 0.714
## ada : Type I error: 0.02349869
```

The package also implemented a generic classifier with the scores on each observation needed. An example is follows.


```
fit2 = npc(y = y, score = pred$pred.score, pred.score = pred$pred.score, method = 'custom')
```

Back to Top

## Neyman-Pearson Receiver Operator Curve

The package provides an implementation of Neyman-Pearson Receiver Operator Curve (`nproc`) via the function `nproc`. Here is a brief demo. We use the same data in the NP classifier, i.e., a dataset (x,y) from a logistic regression model with 2 features and sample size 1000. Then, we can call the `nproc` function with a specified classifier.


```
fit = nproc(x, y, method = "svm")  
plot(fit)
```



The implementation with linear discriminant analysis is as follows.

```
fit = nproc(x, y, method = "lda")  
plot(fit)
```


## NP ROC



Another important usage of the package is to create a point-wise confidence interval of ROC curves with a given tolerance probability `delta`. The default `delta = 0.05` corresponds to the 95% point-wise confidence interval. Here is one example.

```
fit = nproc(x, y, method = "logistic", conf = TRUE)
plot(fit)
```


## NP ROC: 0.95 Confidence Curve



The package provides efficient computation of NP ROC curves using several different classifiers. The following compares SVM, logistic regression and linear discriminant analysis with the 95% point-wise confidence interval. It is clear from the graph that logistic regression and linear discriminant analysis perform similarly and are better than SVM.

```
fit = nproc(x, y, method = c('svm','lda'), conf = T)
plot(fit)
```

## NP ROC: 0.95 Confidence Curve



[Back to Top](#)