

# Timings of common tasks using the **data.table** package in R

Matthew Dowle

January 19, 2011

(A later revision may be available on the [homepage](#))

\* WORK IN PROGRESS \*

This document contains a series of tests, followed by a summary table of various timings and comparisons. Please go straight to the summary table first [<here>](#) in which each row has a link back to the test.

This document is reproducible. Simply run the .Rnw file yourself in your environment to confirm the results. Also see `?vignette`, which says that `edit(vignette("datatable-timings"))` will extract the code from this document so you can easily work with it.

The .Rnw included in the package has  $N=10,000,000$ . This is a small number so that 'R CMD build' completes in a reasonable time (about 5 minutes). We don't want the nightly builds on R-Forge and CRAN to slow down just to run long timing comparisons. We have increased this to  $N=100,000,000$  ourselves, and included the output on the [datatable homepage](#) ([<link>](#)).

## Contents

|          |                      |          |
|----------|----------------------|----------|
| <b>1</b> | <b>Timing tests</b>  | <b>1</b> |
| 1.1      | Extraction           | 1        |
| 1.2      | Grouping             | 2        |
| 1.3      | Test 3               | 2        |
| 1.4      | Test 4               | 2        |
| 1.5      | Test 5               | 2        |
| <b>2</b> | <b>Summary table</b> | <b>2</b> |

## 1 Timing tests

### 1.1 Extraction

This is a repeat of the test in section 1 of the Introduction vignette. The syntax is explained there. This demonstrates the large difference in speed between vector scans and binary search. Therefore, please avoid using `==` in the `i` expression.

```
> n = ceiling(1e7/26^2) # 10 million rows
> DF = data.frame(x=rep(LETTERS,each=26*n),
+               y=rep(letters,each=n),
+               v=rnorm(n*26^2))
> DT = data.table(DF,key="x,y")
> tables()
```

```
      NAME      NROW MB COLS KEY
[1,] DT    10,000,068 153 x,y,v x,y
Total: 153MB
```

```
> tt=system.time(ans1 <- DF[DF$x=="R" & DF$y=="h",]); tt
```

```

      user  system elapsed
5.241    1.412    6.653

> ss=system.time(ans2 <- DT[J("R","h"),mult="all"]); ss

      user  system elapsed
0.008    0.000    0.008

> mapply(identical,ans1,ans2)

      x      y      v
TRUE TRUE TRUE

```

## 1.2 Grouping

This is a repeat of the test in section 2 of the Introduction vignette. The syntax is explained there.

```

> ttt=system.time(ans1 <- tapply(DF$v,DF$x,sum)); ttt

      user  system elapsed
5.300    1.332    6.633

> sss=system.time(ans2 <- DT[,sum(v),by=x]); sss

      user  system elapsed
0.248    0.220    0.467

> identical(as.vector(ans1), ans2$V1)

[1] TRUE

```

## 1.3 Test 3

## 1.4 Test 4

## 1.5 Test 5

# 2 Summary table

```

> ans

      base data.table times faster
==    6.653      0.008      831
tapply 6.633      0.467      14

> toLatex(sessionInfo())

• R version 2.12.1 Patched (2011-01-18 r54032), x86_64-unknown-linux-gnu

• Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_US.UTF-8, LC_COLLATE=C,
  LC_MONETARY=C, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_US.UTF-8, LC_NAME=C,
  LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_US.UTF-8, LC_IDENTIFICATION=C

• Base packages: base, datasets, grDevices, graphics, methods, stats, utils

• Other packages: data.table~1.5.2

• Loaded via a namespace (and not attached): tools~2.12.1

```